



Key Feature

- 2-wire plug & play, easy, cost-efficient
- Receive video call and unlock via indoor station
- 7-inch TFT screen with 1024 \times 600 resolution

Specification

System parameters				
Operating	Embedded Analog operation system			
system	Embedded Analog operation system			
ROM	/			
RAM	/			
CPU	/			
Display parameters				
Screen size	7-inch			
Operation	Non-touch			
method				
Туре	TFT screen			
Resolution	1024 × 600			
Video parameters				
Video standard	1			
Lens	/			
FOV	/			
WDR	1			
Resolution	/			
Focal length	/			
Audio parameters				
Audio				
compression	/			
standard				


Audio input	Built-in omnidirectional microphone				
Audio output	Built-in loudspeaker (more than 80 dB				
Addio odtput	within 20 cm)				
Audio					
compression	/				
bitrate					
Audio quality	/				
Volume	Adjustable with touch buttons				
adjustment					
Capacity					
Linked network	1				
camera capacity	1				
Linked indoor					
extensions	2				
capacity					
Notice capacity	/				
Linked					
doorphone	2				
capacity					
Network parameters					
Communication	/				
protocol	/				
Wired network	1				
Wi-Fi	1				
Bluetooth	1				
3G/4G	1				
Zigbee	/				
Device interfaces					
Alarm input	/				
TAMPER	/				




Network interface	/		
RS-485	/		
USB	1		
TF card	/		
Alarm output	1		
Power interface	3 two-wire interfaces, 2 interfaces supply for door stations, 1 interface supply for indoor extension.		
DIP switch	2, ring duration can be set via DIP switch		
General			
Button	6 touch buttons		
Installation	Surface mounting		
Indicator	/		
Weight	With package: 874.4 g Without package: 334.6 g		
Protective level	1		
Power supply method	1		
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)		
Working humidity	10% to 90%		
Dimensions	187 mm $ imes$ 137 mm $ imes$ 25.4 mm (7.36" $ imes$ 5.39" $ imes$ 1.00")		
Battery	/		

3	Volume +	10	Loudspeaker
4	Volume -	11	Power
			Terminal
5	Receive/Dec	12	DIP Switch
	line		
6	Unlock Door	13	Debugging
	2		Port
7	Unlock Door		
	1		

Dimension





Available Model

DS-KH1200

Power supply
Application

environment


consumption


Power

Physical Interface

Indoor

 \leq 5 W





No.	Description	No.	Description
1	Screen	8	Monitor/Swi
			tch
2	Microphone	9	Terminals



Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T+86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T+99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2020 | Data subject to change without notice |