

Baseline product line

Hub Plus Jeweller

Control panel supporting Ajax wireless devices









Jeweller

communication technology

- Up to 2,000 m of radio communication in an open space
- Data is encrypted throughout the transmission process
- Auto adjustment of radio signal strength to reduce interference and devices' power consumption
- Regular polling to display current devices' statuses



Always online

- 4 communication channels: Ethernet, Wi-Fi, and 2 SIM cards that support 3G/2G
- The communication channels work simultaneously instant switch
- 99.99%¹ uptime of Ajax Cloud server



Features

- Up to 100 Ajax devices in the system
- Up to 32 automation scenarios
- Up to 25 cameras and DVRs²



Sabotage resistance

- Tamper alarm
- Notifications of jamming
- Detection of the connection loss with devices within 36 seconds³
- Up to 16 hours of battery life in case of power loss⁴

Quick installation and setup

- Connecting to Ajax apps via QR code
- Remote control and configuration in apps
- Effortless installation and replacement

Compliance with standards	Communication with Ajax devices	Devices	Features
PD 6662:2017 EN 50131 (Grade 2)	Jeweller communication technology Communication range up to 2,000 m In an open space Frequency bands 868.0–868.6 MHz Two-way communication between the hub and connected devices	Up to 100 Ajax wireless devices Including up to 5 range extenders and up to 10 sirens	50 users 32 automation scenarios 25 cameras and NVRs² 9 security groups 50 rooms
Additional features Over-the-air updates Remote control and configuration in the app Types of notifications: SMS, calls, and push notifications	Connection to CMS SurGard (Contact ID) SIA (DC-09) ADEMCO 685 Other proprietary protocols	Communication channels Ethernet, Wi-Fi, and 2 SIM cards: 2G GSM900/DCS1800 (B3/B8) 3G WCDMA 850/900/2100 (B1/B5/B8)	Power supply Main power supply unit 100-240 V, 50/60 Hz Backup power supply Built-in backup battery Li-lon 2 A·h Up to 16 hours of battery life in case of power loss ⁴
Installation Operating temperature range from -10°C to +40°C Operating humidity up to 75% Protection class IP50	Colour white, black Dimensions 163 × 163 × 36 mm Weight 350 g Tamper alarm	Complete set Hub Plus Jeweller SmartBracket mounting panel Power cable Ethernet cable Installation kit SIM cards (depending on region) Quick start guide	

- 1 in 2023.
- 2 third-party cameras and DVRs.
- 3 depends on settings.
- 4 when only GSM works.













For detailed information, scan the QR code or follow the link: