

PoE Midspan 30W

Midspan power supply unit, 1x Ethernet, 10/100/1000Base-T, 802.3at, 802.3af, 30 W, black



Features

- IEEE 802.3at compliant
- IEEE 802.3af compliant
- Output power 30 W
- Supports 10/100/1000Base-T
- Automatic output adaptation
- Compact design

Specifications

- 1x Port
- Data rate 10/100/1000 Mbps
- Shielded RJ-45 connectors, EIA 568A and 568B
- LED indicators AC Power (yellow) and Channel Power (green)
- PoE standards IEEE 802.3at and IEEE802.3af
- Power over Ethernet OUT 55V DC, 30W, pin 4/5 (+), pin 7/8 (-)
- Voltage supply 115/230 V AC $\pm 10\%$, 50/60 Hz
- Dimensions (W x H x L) 53 mm x 33 mm x 140 mm (2.1" x 1.3" x 5.5")
- Weight 200 g (0.44 lbs)
- Operating temperature -20°C to $+40^{\circ}\text{C}$ (-4°F to 104°F)
- Relative humidity 0% – 90%RH, non-condensing
- CE, FCC, UL/cUL, RoHS compliant

Midspan



004316

PoE Midspan 30 W

Midspan power supply unit, 1x Ethernet port, 10/100/1000Base-T, 802.3at, 802.3af, 30 W, black

Dallmeier electronic GmbH & Co.KG | Bahnhofstr. 16, 93047 Regensburg, Germany | +49 941 8700-0 | dallmeier.com

All trademarks identified by * are registered trademarks of Dallmeier electronic GmbH & Co.KG.

Third-party trademarks are named for information purposes only. Dallmeier electronic respects the intellectual property of third parties and always attempts to ensure the complete identification of third-party trademarks and indication of the respective holder of rights. In case that protected rights are not indicated separately, this circumstance is no reason to assume that the respective trademark is unprotected.

Specifications subject to change without notice. Errors and misprints excepted. Pictures may differ from the actual product.



See more.