

INT-SF-B

PARTITION KEYPAD

The **INT-SF-B** partition keypad allows you to control operation of each alarm system based on the control panels of **INTEGRA** and **INTEGRA Plus** families. To maintain a uniform design line of the controls, it is recommended that the INT-SF partition keypad be used in alarm systems including the **INT-KLFR**, **INT-TSI**, **INT-TSG** and **INT-KSG** keypads.

- white color backlight
- controls single partition in the system
- PANIC, FIRE and AUX alarms triggered from keypad
- LEDs for partition status indication
- buzzer for acoustic signaling of selected system events
- access control functions
- relay for electromagnetic lock / electric strike control
- door status monitoring input
- available in white (**INT-SF-W**), black (**INT-SF-B**), light with silver frame (**INT-SF-SSW**), dark with silver frame (**INT-SF-BSB**) and white with silver frame (**INT-SF-WSW**)



TECHNICAL DATA

| | |
|--|------------------|
| Supply voltage | 12 V DC |
| Operating temperature range | -10°C...+55°C |
| Standby mode current consumption | 20 mA |
| Max. current consumption | 40 mA |
| Weight | 180 g |
| Maximum humidity | 93±3% |
| Dimensions | 80 x 143 x 25 mm |
| Environmental class according to EN50130-5 | II |
| Relay output (resistive load) | 1 A / 30 V DC |

