

High-Performance Desktop Power Supply DC 12V 2A



Model: NPS-D112D-2A-CCTV

Main Features:

- ✧ Wide AC input range: 90-264 VAC;
- ✧ LED indicator for power status;
- ✧ No load power consumption ≤ 0.2 W;
- ✧ Low ripple & noise and low temperature rise;
- ✧ Short Circuit / Over Voltage / Over Current Protection.

Input

Input Range	90-264 VAC, 47-63 Hz
AC Current	≤ 1 A
Efficiency	$\geq 82\%$
Inrush Current	cold start max. 30 A at 240 VAC
Leakage Current	< 3 mA at 240 VAC

Output

Output Voltage	12 VDC ($\pm 5\%$)
Rated Current	2 A
Line Regulation	$\pm 3\%$
Load Regulation	$\pm 5\%$
Ripple & Noise	≤ 120 mVp-p
Setup, Rise, Hold-up time	700ms, 40ms, 5ms at 230 VAC; 1000ms, 40ms, 5ms at 115 VAC

Environment

Operating Temperature	-20°C to 50°C
Operating Humidity	RH 10% to 96% (non-condensing)
Storage Temperature	-40°C to 80°C
Storage Humidity	RH 5% to 96% (non-condensing)
Withstand Vibration	Standard: IEC 721-3-3 3M3, 5~9 Hz, A=1.5 mm; 9~200 Hz, acceleration 5 m/s ²
Transportation Vibration	Standard: IEC 721-3-2 2M2, 5~9 Hz, A=3.5 mm; 9~200 Hz, acceleration 5 m/s ² ; 200~500 Hz, acceleration 15 m/s ²

Safety

Withstand Voltage	1.5 kVAC
Insulation Resistance	$\geq 100 \text{ M}\Omega$ at 500 VDC
EMC Standard	EN55032, EN61000-3-2, EN61000-3-3, EN55035

General

Dimension	129x56x33 mm (LxWxH)
DC Connector	DC Plug 5.5x2.1 mm
Net Weight	200 g
Gross Weight	400 g (AC power cord included)
Package List	1x Power Supply, 1x AC Power Cord

Diagram

