

SLIM-PIR-PET

PIR MOTION DETECTOR WITH PET IMMUNITY UP TO 20 KG

SLIM-PIR-PET detects motion in the protected area.

- compliance with EN 50131 requirements for Grade 2
- motion detection using passive infrared (PIR) sensor
- adjustable sensitivity of detection
- digital motion detection algorithm
- digital temperature compensation
- wide-angle lens, designed specifically for the **SLIM LINE** detectors
- pet immunity up to 20 kg
- built-in end-of-line resistors (2EOL: 2 x 1.1 k Ω)
- LED indicator
- selectable color of the LED indicator (4 colors available)
- LED indicator remote enable/disable
- supervision of motion detection and supply voltage circuit
- tamper protection against opening of enclosure



TECHNICAL DATA

Supply voltage	12 V DC
Detected target velocity	0,3...3 m/s
Operating temperature range	-10°C...+55°C
Recommended mounting height	2,4 m
Standby mode current consumption	8 mA
Max. current consumption	23 mA
Weight	100 g
Maximum humidity	93±3%
Dimensions	62 x 137 x 42 mm
Environmental class according to EN50130-5	II
Alarm signaling time	2 s
Complied with standards	EN 50131-1, EN 50131-2-2, EN 50130-4, EN 50130-5
EOL resistors	2 x 1,1 k Ω
Warm-up period	30 s
Security grade according to EN50131-2-2	Grade 2
Detection area	12 m x 13 m, 90°
Alarm outputs (NC relay, resistive load)	40 mA / 24 V DC
Tamper outputs (NC)	100 mA / 30 V DC

